

# Specifications Metric

	Refrigerator	Interior	Freezer	Weight	Cut Out	Flange	Panel Single Door	Light	Options see index below	Amperage Running* 12/24vdc
	Single Door	Volume Liters	Volume Liters	KG	H x W x D mm	Dimension H x W mm	H x W mm			
	R1200	34	n/a	17	628x355x368-406	648x384	540x320	N/A		2.2 / 1.1
S/O	R1600	36	4	16	524x397x349	543x415	512x386	N/A		2.2 / 1.1
	R1900	54	6	18	524x397x450	543x415	512x386	N/A		2.2 / 1.1
	R2300	59	7.1	20	721x425x356	742x451	712x421	N/A	(CH)	2.2 / 1.1
	R2600	68	4	18	514x457x495	533x476	513x440	N/A		2.2 / 1.1
	R3000	70	7.1	20.5	626x488x419	647x513	609x482	N/A		2.2 / 1.1
	R3100	85	8.5	22	721x425x495	742x451	712x421	S	(CH)	2.2 / 1.1
	R3800	100	12.7	24.5	721x514x457	745x536	712x499	S	(CH)(FL)	2.2 / 1.1
	R4500	122	17	27	721x514x533	745x536	712x499	S	(CH)(FL)	4.4 / 2.2
	R5810	164	11.3	31	809x590x597 to 559	829x622	752x543	S	(FL)	4.4 / 2.2

### Freezer Single Door

	F1200	34	34	17	628x355x368-406	648x384	540x320	N/A		4.4 / 2.2
	F1900	54	54	18	524x397x450	543x415	512x386	N/A		4.4 / 2.2
	F2300	59	59	22	721x425x356	742x451	712x421	N/A	(CH)	4.4 / 2.2
	F2600	68	68	19.5	514x457x495	533x476	513x440	N/A		4.4 / 2.2
	F3100	85	8.5	22	721x425x470	742x451	712x421	N/A	(CH)	2.2 / 1.1
	F3800	100	100	26	721x514x457	742x533	712x499	N/A	(CH)	4.4 / 2.2
	F5810	164	164	31	809x590x597 to 559	829x622	752x543	N/A		5.2 / 2.6

### Top Loading

	TL2500	71		26	476-686x514x457	533x476	513x440	N/A		4.4 / 2.2
--	--------	----	--	----	-----------------	---------	---------	-----	--	-----------

	Refrigerator	Interior	Freezer	Weight	Cut Out	Flange	Panel Single Door	Panel	Light	Options see index below	Amperage Running* 12/24vdc
	Two Door Side x Side	Volume Liters	Volume Liters	KG	H x W x D mm	Dimension H x W mm	H x W mm	Two Door H x W mm			
N/A	RS4600	119	14.1	36	721x873x356	747x902	712x421	712x421	N/A	(CH)(FL)	4.4 / 2.2
N/A	RS6100	159	19.8	39	721x962x419	747x988	712x499	712x421	S	(CH)(F)(FL)	4.4 / 2.2
N/A	RS7600	198	22.6	42	721x1048x470	747x1067	712x499	712x499	S	(CH)(F)(FL)	4.4 / 2.2

### Refrigerator Freezer Two Door Side x Side

N/A	RFS6100	159	59	37	721x962x419	747x988	712x499	712x421	S	(CH)(F)	4.4 / 2.2
N/A	RFS6500	181	59	39	721x962x489	747x988	712x499	712x421	S	(CH)(F)	4.4 / 2.2
	RFS7501	212	57	39	864x711x559	889x737	857x236	857x454	S		4.4 / 2.2

### Refrigerator Freezer Two Door Upright

	RFU6209	170	71	42	1203x514x521	1222x533	712x499	438x498	S		5.2 / 2.6
N/A	RFU6400	193	51	38	1194x514x502	1206x540	712x499	267x495	S		5.2 / 2.6
	RFU6809	193	71	43	1203x514x546	1222x533	712x499	438x498	S		5.2 / 2.6
U/T/A	RFU7300**	192	48	38.6	1473x425x476	1486x451	914x421	368x421	S		3.5 / 1.8
N/A	RFU8320	206	45	43	1155x591x552	1168x629	752x543	336x543	S		5.2 / 2.6
	RFU8250**	206	45	43	1343x591x495	1356x629	752x543	336x543	S		5.2 / 2.6
	RFU9009	258	70.8	48	1343x591x578	1356x629	752x543	336x543	S		5.2 / 2.6

### Two Door Upright Refrigerator

N/A	RU7600	200	25.4	49	1467x502x457	1486x536	712x499	712x499	S		4.4 / 2.2
-----	--------	-----	------	----	--------------	----------	---------	---------	---	--	-----------

\*Note: The amperage listed is while the unit is running. To determine 24hr consumption calculate the run time for 24hrs and multiply this by the listed amperage. Listed amperage will change with ambient temperature and unit door openings.

\*\*Note: The RFU7300, RFU8250, RFU9200 (Same as RFU9009) is a two compressor model; the amperage is 3.5 per compressor

		Key	
		N/A	Not Available
		U/T/A	Untested AUS Conditions
B	Options Index	S/O	Special Order
CH (Special Order)	Black frame	O	Optional
F (Special Order)	Chine hugger	S	Standard
FL	Flush mounting frame kit		
	Flat cooling plate all refrigerator no freezer		